


TWIN BOOTLACE FERRULES



Aftec Twin bootlace ferrules ensure reliable electrical connectors when terminating conductors in screw clamp terminal blocks and are used for twin wire containment. Color coding of the insulation is according to the wire size and the country standard. Designed with seamless barrel to contain loose wire strands for separator terminations which are easy to use by stripping the wire and sliding on to the end wire and crimping suitable for limited space panel applications.

Technical Data	
Material	Copper
Finish	Tin Plated
Insulation	Vinyl

* Technical Information is Subject to change without notice.



MODEL NO.	WIRE RANGE		COLOUR (STANDARDS)			DIMENSIONS (mm)					
	mm	AWG	FRE	GER	DIN	F	L	W	B	D	C
ABF 0.5 - 8 X 2C	2 X 0.5	2 X 22	WHITE	ORANGE	WHITE	8	14.50	5.00	6.50	1.80	1.50
ABF 0.75 - 10 X 2C	2 X 0.75	2 X 20	BLUE	WHITE	GRAY	10	16.70	5.50	6.70	2.10	1.80
ABF 1.0 - 10 X 2C	2 X 1.0	2 X 18	RED	YELLOW	RED	10	17.10	5.50	7.10	2.30	2.00
ABF 1.5 - 8 X 2C	2 X 1.5	2 X 16	BLACK	RED	BLACK	8	15.50	6.40	7.50	2.60	2.30
ABF 1.5 - 12 X 2C			12	19.50							
ABF 2.5 - 10 X 2C	2 X 2.5	2 X 14	GREY	BLUE	BLUE	10	18.50	8.00	8.50	3.30	2.90
ABF 2.5 - 13 X 2C			13	21.50							
ABF 4 - 12 X 2C	2 X 4	2 X 12	ORANGE	GRAY	GRAY	12	23.10	8.80	11.10	4.20	3.80
ABF 6 - 14 X 2C	2 X 6	2 X 10	GREEN	BLACK	YELLOW	14	26.10	9.50	12.10	5.30	4.90
ABF 10 - 14 X 2C	2 X 10	2 X 8	BROWN	IVORY	RED	14	26.60	12.60	12.60	6.90	6.50
ABF 16 - 14 X 2C	2 X 16	2 X 6	IVORY	GREEN	BLUE	14	31.30	19.00	17.30	8.70	8.30

*Tolerance Dimension (mm): (L/F/B) ± 1.00 to 2.00 , (W) ± 0.15 to 0.30 , (D/C) ± 0.10 to 0.20

*Custom colours can be developed upon request